



Attaching a Shoulder Strap to Your Device

Use PRC-Salttillo's universal shoulder strap to comfortably carry your Accent®, NovaRugged™, or Via® device, or VersaWrap™, with you wherever you go. The quick-release connectors allow you to switch between the long and short straps in the strap kit any time you want. Use the buckle adjusters to lengthen or shorten each strap.

What's in the strap kit:



 Straps are potential entanglement or strangulation hazards. Please consider this prior to placing them with device users.

Getting started

Decide whether you want to carry the device in landscape or portrait orientation. Next, decide if you want to use the long strap or short strap. Then attach two loop connectors to the appropriate strap holders on the device.

Strap holders vary by device. These are examples only. The strap holders on your device may look different. The process of attaching the loop connectors is the same.



Attach the loop connectors and straps

- 1 Thread a loop connector through one of the strap holders on the device. Feed the forked end of the connector through the loop.



- 2 Pull the forked end completely through the loop.



- 3 Pull the loop connector tight on the holder. Repeat steps 1 through 3 with the other loop connector.



- 4 Insert one of the loop connectors into one of the long or short shoulder strap connectors until they click and hold together. Repeat step 4 for the other shoulder strap.



- 5 Insert the shoulder strap connectors into the cushioned shoulder pad connectors until they click and hold together.

- 6 Adjust each shoulder strap using the buckle adjusters.

Hint: If you need to switch between the long and short shoulder straps, squeeze the strap connectors to pull the straps loose from the loop connectors attached to the device and the cushioned shoulder pad. Then attach the other straps, following steps 4 through 6.